



## FSI25

Standard	EN ISO 20345:2011
Category	SIP SRC
Size Range	UK 5 - 15   EU 38 - 50
Colour	Tan
Slip Resistance	SRC

**FSI25:** Pull-on unlined rigger boot. Steel toe cap protection. Steel midsole. Dual Density PU/PU outsole. Conforms to EN ISO 20345:2011 Safety Footwear Standards. Safety footwear protection tested to 200 Joules impact. Penetration resistant midsole tested 1100 Newtons. Unisex size range.

<b>Upper</b>	Apollo Print Action Leather	<b>Construction</b>	Injection
<b>Inner Lining</b>	Unlined	<b>Outsole</b>	Dual Density PU/PU
<b>Footbed</b>	Removable EVA Footbed	<b>Weight</b>	800 grams (half pair size 8)
<b>Impact Resistance</b>	200 Joules Steel Toe Cap	<b>Penetration Resistance</b>	Steel Midsole - Min. 1100N

### FEATURES

- ◆ Pull On Durable Safety Rigger Boot
- ◆ Action Apollo Print Leather Upper
- ◆ Unlined
- ◆ Reinforced PVC Heel Support
- ◆ Durable Dual Density PU Outsole
- ◆ Energy Absorbent Heel
- ◆ Antistatic
- ◆ Oil Resistant Outsole

**Care Advice:** To enhance the life & performance of the footwear, upper should be kept clean & dry. Dry/damp cloth or shoe polish/spray to be used as per the need. Sole to be checked and clean regularly to maintain its traction. Any obvious damage in footwear may reduce full protection and must be replaced.