

SPECIFICATION SHEET: FS203



**Dr
Martens**

FS203

Colour	Teak
Size Range	6-13
Standard	EN345
Category	SB-P-WRU-HRO

Griptrax Waterproof Rigger Boot with excellent slip resilience. The teak oiled and tumbled leather upper and Nitrile Rubber/PU Sole is both water penetration resistant and resistant to high heat temperatures. FS203 features a protective scuff cap and pull-on loops. Steel toe cap and steel midsole protection conforming to best safety practice.

Features

Benefits

EN345 tested.	Conforms to EN345 Safety Footwear Standard.
SB-P-WRU-HRO	Toe protection tested to 200 joules impact. Penetration Resistance 1100 Newtons. Water Penetration Resistant Uppers. Resistance to High Heat 300°C.
Nitrile Rubber/PU Sole	Hardwearing Nitrile rubber outsole combined with cushioned polyurethane midsole. Steel Shank. Energy absorbing heel. Oil and abrasion resistance. Cemented to base of upper.
Slip Resistance	Meets or exceeds ASTM F1677-96 (Mark II Machine) a value of 0.25 as a safety margin for soiling tested on oily, greasy, icy, soapy, or oily/wet surfaces.
Pull-on Loops	Allows the wearer to put on or remove footwear with speed and ease. Particularly if wearing protective gloves.
Scuff cap	Guards the toe cap, giving a longer boot life.

FOOTSURE WESTERN LTD