

FOOTSURE

THE SAFETY FOOTWEAR SPECIALISTS

SPECIFICATION SHEET: FORMATION LO



FORMATION LO

Colour	Black
Size Range	6-12
Standard	ISO20345
Category	S1-P
Slip Rating	SRX

Non-metallic safety trainer with composite toe cap and midsole protection. Breathable nubuck/mesh upper with durable toe wrap. Features five main eyelets plus an additional non-metallic eyelet at the top for an extra-secure fit. A loop is included on the padded tongue for correct alignment, and there is a handy pull-on loop at the back for ease of change. Precisely contoured heel with energy absorbing properties supporting the body's natural gait cycle. Light industrial occupations.

Features

Benefits

ISO20345	Conforms to ISO20345 Safety Footwear Standard.
S1-P	Toe protection tested to 200 joules impact. Safety Footwear Leather Upper plus Antistatic and Energy Absorbing Heel. Penetration Resistance 1100 Newtons.
SRX Slip Resistance Rating	SRX has been developed to meet the needs of the service worker with best-in-class slip resistance. Through enhanced compounding in the outsole, SRX outperforms the competition and exceeds industry standards for slip test.
Rubber/EVA Sole	Ethylene vinyl acetate is a polymer used to absorb physical shock. EVA is combined with rubber in the midsole for its light, flexible and resilient cushioning. Features removable EVA sock liner.
Composite Cap/Midsole	Non-metallic and considerably lighter compared to steel.

FOOTSURE WESTERN LTD

Units F & G, Quedgeley West Business Park, Bristol Road, Hardwicke, Gloucester. GL2 4PH.
T: 01452 727300 (general) 01452 727301 (orders) F: 01452 727305 E: sales@footsure.net W: www.footsure.net