

# HAMMER COLLECTION



## AS263 GRIT

Standard	EN ISO 20345:2022
Category	S3 HRO SRC
Size Range	UK 6 - 13   EU 40 - 48
Colour	Brown
Slip Resistance	SRC



**AS263 GRIT—Hammer Collection:** The AS263 Grit is an outdoor-inspired lightweight steel toe safety dealer boot with a leather upper and a non-metallic anti-penetration midsole. Features a black leather foxing rand and a supportive moulded TPU heel chassis for extra reinforcement. Elasticated side gussets and industrial strength twin pull loops for easy donning and doffing. All day comfort is given via a cushioning, removable PU footbed and a shock absorbing anti-fatigue athletic EVA midsole. Non-marking quality rubber outsole with heat resistance to 300 degrees. Antistatic construction.

<b>Upper</b>	Cow Nubuck Leather & Suede	<b>Construction</b>	Cemented
<b>Inner Lining</b>	Breathable Mesh	<b>Outsole</b>	EVA/Rubber
<b>Footbed</b>	Removable Moulded PU	<b>Weight</b>	750 grams (half pair size 8)
<b>Impact Resistance</b>	200 Joules Steel Toe Cap	<b>Penetration Resistance</b>	Anti-Penetration Non-Metallic Midsole - Min. 1100N

### FEATURES

- ◆ Water resistant full grain crazy horse leather upper
- ◆ Black leather foxing on upper to reinforce and provide extra durability
- ◆ Moulded TPU heel chassis to enhance support
- ◆ Elasticated side gussets for easy foot entry
- ◆ Durable twin pull loops for easy on and easy off
- ◆ Comfortable, cushioned and removable PU footbed
- ◆ Lightweight athletic EVA midsole enhances all day comfort and shock absorption - Reducing fatigue
- ◆ Quality Rubber outsole with technical tread pattern to provide excellent traction, durability and wear performance. Non-marking Rubber outsole.
- ◆ Outsole heat resistant to 300 degrees.
- ◆ Antistatic. Energy absorbing heel.

**Care Advice:** To enhance the life & performance of the footwear, upper should be kept clean & dry. Dry/damp cloth or shoe polish/spray to be used as per the need. Sole to be checked and clean regularly to maintain its traction. Any obvious damage in footwear may reduce full protection and must be replaced.