



Light

ECOFITZ S1P LOW

ECOFITZS1P

2nd Generation of FITZ S1P With GRS Certified Recycled Upper For Light Working Environments

Upper	Knitted Recycled Textile
Lining	Recycled Mesh
Footbed	SJ foam footbed
Midsole	Steel
Outsole	PU
Toecap	Steel
Safety standard	S1P / GRS, ESD, FO, SR
Size range	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
Sample weight	0.613 kg
Norms	ASTM F2413:2018 EN ISO 20345:2022 (Europe)




NAV



BLK



GRY



Breathable upper

Increased moisture and temperature management for extended wearer comfort.



Steel toecap

Robust metal support to protect the feet of the wearer against falling or rolling objects.



Steel midsole

Puncture resistant steel midsoles are made from stainless or coated steel and prevent sharp objects from penetrating the outsole.



SJ Foam

Removable comfortable antistatic footbed providing fit, guidance and optimum shock absorption in heel and forefoot. Breathable and moisture absorbing.



SRC slip resistance

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.

Industries:

Automotive, Construction, Logistics, Industry

Environments:

Dry environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	Knitted Recycled Textile			
	Upper: permeability to water vapor	mg/cm ² /h	37	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	88	≥ 15
Lining	Recycled Mesh			
	Lining: permeability to water vapor	mg/cm ² /h	54	≥ 2
	Lining: water vapor coefficient	mg/cm ²	288	≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	PU			
	Outsole abrasion resistance (volume loss)	mm ³	91	≤ 150
	Outsole slip resistance SRA: heel	friction	0.47	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.51	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.20	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.24	≥ 0.18
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	friction	N/A	≥ 0.31
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	friction	N/A	≥ 0.36
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	friction	N/A	≥ 0.19
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	friction	N/A	≥ 0.22
	Antistatic value	MegaOhm	408	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	29	≥ 20
Toecap	Steel			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	N/A
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	N/A
	Impact resistance toecap (clearance after impact 200J)	mm	17.5	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	19	≥ 14

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.