



FS219	
Standard	EN ISO 20345:2011
Category	SIP SRC
Size Range	UK 4-14 EU 37-14
Colour	Black
Slip Resistance	SRC

FS219: FS219 is a safety rigger with steel midsole and toe cap protection. Benefits from its functional draw-cord and easy adjustable cord-lock, preventing water and debris entering the boot. The hardwearing PU/TPU sole extends to offer bump cap protection against scuffing and the upper is reinforced at the heel. The sole is antistatic and provides first-class energy absorbing qualitites in the heel strike area, reducing daily foot fatigue. Crafted with a full grain crazy horse leather upper that includes Amblers Safety warm-lining recommended for cool conditions or high activity levels. This degree of insulation would best serve those participating in activities that are more rigorous. Added heel kick panel for ease of change. Available in a unisex size range.

Upper	Full Grain Crazy Horse Leather	Construction	Injection
Inner Lining	Faux Synthetic Fur	Outsole	Dual Density PU/TPU
Footbed	Removable PU Footbed	Weight	875 grams (half pair size 8)
Impact Resistance	200 Joules Steel Toe Cap	Penetration Resistance	Steel Midsole - Min. 1100N

FEATURES

- Hardwearing and Rugged Safety Rigger Boot
- Water Resistant Full Grain Crazy Horse Leather Upper
- Warm Faux Fur Lining
- Extended Mesh Upper with Functional Draw Cord and 2 Strong Leather Loops
- Padded Ankle Support
- Injected Moulded PU Scuff Cap

- Reinforced PVC Heel Support
- Injected PU Midsole
- Durable and Hardwearing TPU Outsole
- Energy Absorbent Heel
- Antistatic
- Oil Resistant Outsole
- Non-Marking Outsole