



Amblers Safety is a leading British safety footwear brand, providing all-day comfort and quality. With over 30 years' expertise, we know how to protect you at work with footwear that you can rely on. **TOUGH WORKING COMFORT**



AS308C FRISTON

Standard	EN ISO 20345:2011
Category	S3 WR SRC
Size Range	UK 4 - 14 EU 37 - 49
Colour	Honey, Brown, Black
Slip Resistance	SRC



AS308C FRISTON: Lightweight, metal free safety boot with **DRI-BLOC™** waterproof, breathable membrane to keep feet dry in wet conditions. Water-resistant leather upper with deep padded collar and tongue. Industrial lace up front with rear pull loop for easy donning. Features anti-scuff toe and heel for added durability. SRC-rated antistatic Dual Density PU/PU outsole.

Upper	Water Resistant Nubuck and Crazy	Construction	Injection
Inner Lining	Breathable Waterproof Membrane and	Outsole	Dual Density PU/PU
Footbed	Removable Moulded PU	Weight	675 grams (half pair size 8)
Impact Resistance	200 Joules Fibre Glass Composite Toe Cap	Penetration Resistance	Non-Metallic Anti-Penetration Midsole - Min. 1100N

FEATURES

- ◆ Metal free waterproof safety boot
- ◆ Water resistant leather upper
- ◆ Deep padded breathable mesh collar and tongue
- ◆ Metal free hooks for lacing
- ◆ Comfortable and cushioned removable PU footbed with arch support
- ◆ Anti-scuff toe and heel
- ◆ Dynamic and raised injected PU midsole clasps the upper to provide increased protection.
- ◆ Raised heel for enhanced comfort and stability to provide excellent energy absorption.
- ◆ Cleated outsole provides ultimate performance and grip in varied conditions.
- ◆ Ladder grip lines for working at heights.
- ◆ Non-marking outsole. Fuel & oil resistant outsole.
- ◆ Antistatic. Energy absorbent heel.

Care Advice: To enhance the life & performance of the footwear, upper should be kept clean & dry. Dry/damp cloth or shoe polish/spray to be used as per the need. Sole to be checked and clean regularly to maintain its traction. Any obvious damage in footwear may reduce full protection and must be replaced.