



AS722C (Relay)

Standard	EN ISO 20345:2022
Category	SI PL HRO SR (ESD)
Size Range	UK 4 - 13 EU 37 - 48
Colour	Black
Slip Resistance	SR

**VEGAN
FRIENDLY**

AS722C (Relay): Relay is a lightweight, fully, non-metal safety hiker. It features a mesh upper embossed with Thermoplastic Polyurethane (TPU) and a padded mesh collar ensures all day long comfort. The cushioned removable PU footbed is designed with arch support. The Ethylene-vinyl acetate (EVA) midsole offers enhances comfort and shock absorption. It has a highly durable rubber outsole that is heat resistant to 300° C. Electrostatic discharge is dissipative (ESD). The Relay is an antistatic boot.

Upper	Mesh with Embossed TPU	Construction	Cemented
Inner Lining	Breathable mesh	Outsole	EVA/Rubber
Footbed	Removable Moulded PU	Weight	675 Grams (Half Pair UK Size 8)
Impact Resistance	200 Joules Fibre Glass Composite Toe Cap	Penetration Resistance	Anti-penetration Non-Metallic Midsole - Min. 1100N

FEATURES

- ◆ Lightweight Fully Non-Metal Safety Hiker
- ◆ Features a Thermoplastic Polyurethane (TPU) bonded, breathable mesh upper
- ◆ A mesh collar ensures all day long comfort
- ◆ The cushioned removable PU footbed is designed with arch support
- ◆ The Ethylene-vinyl acetate (EVA) midsole offers an enhanced comfort and shock absorption
- ◆ Durable rubber outsole
- ◆ The outsole is heat resistant to 300°C
- ◆ Electrostatic discharge is dissipative (ESD)
- ◆ Antistatic boot
- ◆ Non-leather upper

Care Advice: To enhance the life & performance of the footwear, upper should be kept clean & dry. Dry/damp cloth or shoe polish/spray to be used as per the need. Sole to be checked and clean regularly to maintain its traction. Any obvious damage in footwear may reduce full protection and must be replaced.